



20X



Value-packed performance and reliability for small delivery vehicles.

PERFORMANCE SPECIFICATIONS

20X



Condenser

Dimensions:
34.01" x 18.89" x 8.42"
(864 x 480 x 214 mm)



Evaporator

Dimensions:
33.58" x 23.93" x 6.77"
(853 x 608 x 172 mm)



CAB COMMAND™

Dimensions:
3.4" x 2.4" x 1.1"
(85 x 60 x 28 mm)

Cooling/Temperature Capacity
Ambient at 100°F (38°C)
Compressor Speed: 2,400 rpm

Evaporator Return Air Temp.	Road Operation	
	BTUH	Watts
35°F (2°C)	7200	2110
0°F (-18°C)	4700	1380

Warranty:

Product warranty and limitations are outlined in Form 62-11019. This warranty applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere.

Specifications are subject to change without notice.

Standard Features Include:

- EasyReach™ condenser
- Durable DuraShell™ composite skin
- Extra-flat SlimLine™ evaporator
- 8 CID (131 cc) six-cylinder swash plate compressor
- Double-A groove clutch
- Non-ozone-depleting R-404A
- Brushless evaporator fan motor
- Hot gas defrost
- Hot gas heating
- Condenser valve enhanced heating circuit
- Refrigerant injector
- Roofmount installation kit
- Low refrigerant pressure protection
- High refrigerant pressure protection
- Microprocessor control system
- CAB COMMAND™ remote control center
- Red light visual warning (in cab)
- Main On/Off system power keys
- Timed defrost interval
- Manual defrost key
- Diagnostic safety indicators
- Frozen range lockout
- Digital readout
- CAB COMMAND™ (in cab)
- Adjustable display brightness
- Current and stored alarms
- Automatic defrost control
- Programmable defrost timer
- Automatic defrost termination
- Manual defrost override
- Installation package
- Refrigerant discharge muffler
- SureTight™ refrigerant hoses
- SureTight™ hose clamps

Accessories and Options:

- Poly-V groove clutch
- Variable groove clutch
- Rear port adapter

Approximate Weights:

- Condenser 66 lb (30 kg)
- Evaporator 37 lb (17 kg)



North America
Carrier Transicold
700 Olympic Drive
Athens, GA 30601 USA
Tel: 706-357-7223
Fax: 706-355-5435

**Central America
and Mexico**
Ejercito Nacional No. 418
Piso 9, Torre Yumal
Col. Chapultepec Morales
11570 Mexico, D.F.
Ph: (5255) 9126.0300
Fax: (5255) 9126.0383



Carrier

A United Technologies Company

Carrier Transicold Division
Carrier Corporation
Truck/Trailer Products Group
P.O. Box 4805
Syracuse, NY 13221 USA

www.trucktrailer.carrier.com